

SUPRACASE

CASINGS

TRUSTWORTHY PACKAGING



GMC GMD
CASINGS
FOR MOLDS

SMT
CASINGS
FOR STERILISATION

SMS
CASINGS WITH
EVOH LAYER

	ONE-LAYER CASINGS	FIVE-LAYER CASINGS			SEVEN-LAYER CASINGS	
SYMBOL	GOL GOX	GML GMX	GMC GMD	SMT	GMS	SMS
COMPOSITION	PA	PA/PE/PA	PA/PE/PA	PA/PP/PA	PA/PE/PA	PA/EVOH/PE/PA
THERMOSHRINKABILITY (%)	10	10	14	13	10	10
THERMAL RESISTANCE (°C)	-20 / +125	-20 / +90	-20 / +90	-20 / +125	-20 / +90	-20 / +90
SUGGESTED TIME OF STORING A PACKED PRODUCT	up to 45 days	up to 90 days	up to 90 days	up to 90 days for unsterilised products	up to 30 days	up to 120 days

APPLICATION

- Unsmoked sausages and sausage products
- Delicatessen
- Cheese spreads
- Soups and sauces
- Pressed meat blocks
- Pet food
- Products for sterilisation


ADVANTAGES

- High barrier to gases and aromas
- Very low permeability of water vapour
- High mechanical strength
- High thermal resistance
- Constant thermoshrinkability
- Variety of calibres and colours


WE OFFER



SURFACE PRINT



SHIRRING



VARIETY OF CALIBRES

WE DESIGN SOLUTIONS ACCORDING TO INDIVIDUAL CUSTOMER NEEDS